

MS

Antivibrante Sgolato Maschio/Maschio

Sand-Glass Mounting Double Male

Cod.	A	B	M	D	E	Carico max a Compres. Max Compression Load daN	Carico max a Taglio Max Shear Load daN
A2MS12	12	15	04MA	7	10	3	0,8
A2MS25	25	20	06MA	10	18	50	3
A2MS30	30	20	08MA	20	20	60	10
A2MS40	40	30	08MA	19	20	80	6
A2MS40L	40	30	08MA	27	20	100	8

Caratteristiche

Materiale corpo: Mescola gomma NR/SBR

Durezza standard: 60 shore A

Tolleranza sulla durezza: +/- 5 SH

A richiesta: Differenti lunghezze della vite

Parte metallica e/o fissaggio:

Vite e rondella zincate

Tipo inserto standard:

Vite pressata sulla rondella

Product specification

Main part material:

NR/SBR rubber compound

Standard hardness: 60 shore A

Hardness tolerance: +/- 5 SH

On request: Different screw lengths

Metallic part: Zinc plated screw and washer

Standard thread:

Screw pressed on the washer

—
Per art. MS e CN misure e durezza producibili su richiesta, rivolgersi all'ufficio commerciale. La quota "E" può essere soggetta a variazioni senza preavviso.

—
For art. MS and CN other sizes or hardnesses can be produced on demand. For information please contact our sales department. Dimension "E" can vary without notice.

